

IN THE CLAIMS:

1. (Previously Presented) An astragal assembly for attachment to a passive door having an interior surface, an exterior surface opposite to the interior surface, and an outer edge extending from the exterior surface to the interior surface, comprising:

a metallic rail having an exterior portion, an interior portion spaced from and opposed to the exterior portion, and a side portion extending between the exterior portion and the interior portion and forming an angle with each of the exterior portion and the interior portion, and a spacer extending outwardly from the side portion away from the exterior portion and the interior portion of the metallic rail and having a distal end to maintain an air gap between a surface of the outer edge of the passive door and the side portion of the metallic rail when the astragal assembly is affixed thereto to allow air flow between the outer edge of the passive door and the side portion of the metallic rail, wherein an elongated open channel is defined in the metallic rail with sides formed by the exterior portion and the interior portion and a base formed by the side portion, the elongated open channel having an opening extending between the exterior portion and the interior portion and opposed to the side portion; and

a wooden insert retained within the elongated open channel in the metallic rail.

2. (Original) The astragal assembly of claim 1, wherein the wooden insert extends substantially the entire length of the elongated open channel.

3. (Original) The astragal assembly of claim 1, wherein the wooden insert is a solid piece of wood.

4. (Original) The astragal assembly of claim 1, wherein the wooden insert comprises multiple pieces of wooden strips secured within the elongated open channel.

5. (Original) The astragal assembly of claim 1, wherein the wooden insert is elongated and symmetrical about a longitudinal axis.

6. (Original) The astragal assembly of claim 1, wherein the metallic rail includes extruded aluminum.
7. (Original) The astragal assembly of claim 1, wherein the metallic rail comprises aluminum.
8. (Original) The astragal assembly of claim 1, further comprising hardware attached to the wooden insert.
9. (Original) The astragal assembly of claim 8, wherein the hardware includes a strike plate.
10. (Original) The astragal assembly of claim 8, wherein the hardware directly contacts the wooden insert.
11. (Original) The astragal assembly of claim 1, wherein the interior portion includes an interior flange that extends past the side portion for overlapping an interior surface of the passive door.
12. (Original) The astragal assembly of claim 1, wherein the exterior portion includes a stop that extends from one side thereof.
13. (Original) The astragal assembly of claim 12, further comprising a gasket secured to the stop.
14. (Original) The astragal assembly of claim 1, wherein the exterior portion includes an exterior flange that extends past the side portion for overlapping an exterior surface of the passive door.
15. (Original) The astragal assembly of claim 1, wherein the exterior portion includes an exterior flange and the interior portion includes an interior flange, wherein the exterior flange and the interior flange extend past the side portion to define a door edge receiving opening.

16. (Original) The astragal assembly of claim 1, wherein the exterior portion includes a hollow elongate tubular section, wherein the channel is formed between the interior portion and the hollow elongate tubular section.

17. (Original) The astragal assembly of claim 1, wherein the side portion includes a thermal break.

18. (Original) The astragal assembly of claim 1, wherein the side portion includes preformed openings to receive fasteners for connecting the astragal to the passive door.

19. (Original) The astragal assembly of claim 1, wherein the exterior portion and the interior portion each have a hook that extends into the channel and retains the wooden insert.

20. (Original) The astragal assembly of claim 1, wherein the wooden insert includes a first piece having a width substantially equal to a distance between the exterior portion and the interior portion and a second piece abutting the side portion.

21. (Original) The astragal assembly of claim 20, wherein the second piece has a width less than the width of the first piece.

22. (Original) The astragal assembly of claim 1, in combination with a double door system including an active door and a passive door, wherein the side portion of the astragal assembly is fastened to the passive door.

23. (Previously Presented) A door assembly, comprising:

a passive door having an interior surface, an exterior surface opposite to the interior surface, and an outer edge extending from the exterior surface to the interior surface;

an active door having an outer edge, wherein the active door is mounted for movement between an open position and a closed position in which the outer edge is aligned with the outer edge of the passive door;

an astragal coupled to the outer edge of the passive door, wherein the astragal includes a metallic rail having an exterior portion, an interior portion spaced from and opposed to the exterior portion, and a side portion that extends between the exterior portion and the interior portion, and a spacer extending outwardly from the side portion away from the exterior portion and the interior portion of the metallic rail and having a distal end that maintains an air gap between a surface of the outer edge of the passive door and the side portion of the metallic rail to allow air flow between the outer edge of the passive door and the side portion of the metallic rail, wherein an elongated open channel is defined in the metallic rail with sides formed by the exterior portion and the interior portion and a base formed by the side portion, wherein the elongated open channel has an opening extending between the exterior portion and the interior portion and opposed to the side portion, the opening facing away from the outer edge of the passive door, and wherein a wooden insert is retained within the elongated open channel in the metallic rail that faces the active door in the closed position.

24. (Original) The door assembly of claim 23, wherein the astragal includes an interior flange extending from the interior portion and an exterior flange extending from the exterior portion such that the outer edge of the passive door is clamped between the interior flange and the exterior flange.

25. (Original) The door assembly of claim 23, wherein the exterior portion includes a hollow section.

26. (Original) The door assembly of claim 23, wherein the side portion includes a thermal break.

27. (Original) The door assembly of claim 23, further comprising door hardware coupled to the wooden insert.

28. (Original) The door assembly of claim 27, wherein the hardware includes a strike plate.

29. (Original) The door assembly of claim 23, wherein the wooden insert has a U-shaped cross section.

30. (Original) The door assembly of claim 23, further comprising a fastener extending through the wooden insert and the side portion into the outer edge of the passive door.

31. (Original) The door assembly of claim 23, further comprising a gasket coupled to the exterior portion of the astragal that abuts the active door in the closed position.

32. (Previously Presented) An astragal comprising:

an extruded aluminum rail with an exterior portion having an exterior flange extending from a first side and a stop extending from a second side opposite to the first side, an interior portion spaced from and opposed to the exterior portion, and a side portion extending between the exterior portion and the interior portion having a fastening formation, the side portion having a spacer extending outwardly therefrom; and

an insert member retained substantially within a channel in the extruded aluminum rail formed by the exterior portion, the interior portion and the side portion, wherein the insert presents an outer surface for attachment to hardware, and the spacer extends away from the channel.

33. (Previously Presented) The astragal of claim 32, wherein the exterior portion includes a hollow section and a hook extending into the channel that retains the insert member.

34. (Previously Presented) The astragal of claim 32, wherein the interior portion includes a thin wall with a hook extending into the channel that retains the insert member.

35. (Original) The astragal of claim 32, wherein the side portion includes a thermal break.

36. (Previously Presented) The astragal of claim 32, wherein the insert member is wooden.

37. (Previously Presented) The astragal of claim 32, further comprising a strike plate secured to the insert member.

38. (Original) The astragal of claim 32, wherein the extruded aluminum rail has a generally U-shaped cross section, with the side portion including a fastening formation that attaches to a door edge such that the U-shaped cross section faces outward from the door edge.

39. (Previously Presented) The astragal assembly of claim 1, wherein the side portion is opposed to the outer edge of the passive door and is arranged substantially parallel to the outer edge of the passive door, and the exterior portion and interior portion extend away from the outer edge of the passive door.

40. (Currently Amended) An astragal assembly for attachment to a passive door having an interior surface, an exterior surface opposite to the interior surface, and an outer edge extending between the exterior surface and the interior surface, the assembly comprising:

a metallic frame fixable to the exterior surface and the interior surface of the passive door, the metallic frame having an exterior portion adjacent to the exterior surface of the passive door when the astragal assembly is affixed thereto, an interior portion adjacent to the interior surface of the passive door when the astragal assembly is affixed thereto, and a side portion extending between the exterior portion and the interior portion of the metallic frame and opposite to the outer edge of the passive door when the astragal assembly is affixed to the passive door, the interior portion, the exterior portion, and the side portion forming an opening in the metallic frame which faces away from the outer edge of the passive door; and

a wooden insert disposed in the metallic frame between the interior portion, the exterior portion, and the side portion thereof; ~~and~~

~~a hardware component disposed in the wooden insert at the opening in the metallic frame.~~

41. (Previously Presented) The astragal assembly of claim 40, wherein the metallic frame further comprises a spacer extending from the side portion toward the outer edge of the passive door to maintain an air gap between the side portion and the outer edge of the passive door.

42. (Previously Presented) An astragal assembly usable with an active door and a passive door having an exterior surface, an interior surface opposite to the exterior surface, and an outer end disposed between the exterior surface and the interior surface, the assembly comprising:

a frame including an interior portion, an exterior portion spaced apart from and opposed to the interior portion, a side portion extending between the interior portion and the exterior portion opposite to the outer end of the passive door when the astragal assembly is attached thereto, an interior flange extending from where the interior portion meets the side portion to engage the interior surface of the passive door when the astragal assembly is attached thereto, an exterior flange extending from where the exterior portion meets the side portion to engage the exterior surface of the passive door when the astragal assembly is attached thereto, and an channel formed by the exterior portion, the interior portion, and the side portion of the frame; and

an insert member disposed in the channel and having a surface exposed to the active door when the astragal assembly is attached to the passive door.

43. (Previously Presented) The astragal assembly of claim 42, wherein the interior portion and the exterior portion extend away from the outer end of the passive door when the astragal assembly is affixed thereto.

44. (Previously Presented) The astragal assembly of claim 42, further comprising:

a spacer projecting from the side portion of the frame to the outer end of the passive door to maintain a gap between the frame and the passive door when the astragal assembly is attached to the passive door.

45. (Previously Presented) The astragal assembly of claim 42, wherein the insert member is wooden and the frame is metallic.

46. (New) The astragal assembly of claim 40, further comprising:
a hardware component disposed in the wooden insert at the opening in the metallic frame.